

## Baselift 6310HA - 219,0 cm



**BASELIFT 6310HA** is a straight, motorised worktop lift with floor-mounted motors. Under the worktop, space is left for the knees and legs. Installations under the worktop (motors, water, sewers) can be concealed by telescopic cover panels which gives the kitchen a neat look. The motors work steplessly and adjust the worktop quickly and quietly to the desired height. The lift is equipped with a reliable safety system that guarantees safe operation without any risk of pinching. The lift is prepared in the factory to facilitate easy installation.

The lift can be integrated in kitchens from any kitchen manufacturer.

### Functions and advantages

- Can be equipped with drawers, hob and sink
- 30 cm height adjustment
- Adjustable depth, 56 – 59 cm from wall
- Frame in aluminium. Prepared from factory. Movable (sideward) and angle adjustable consoles.
- Electronic and motor system "Plug and Play"
- Safety strip covers the front edge under the worktop. (Installed from factory)
- Brackets and screws for installation of fronts and worktop are included in the delivery

### Useful information

- The worktops depth must be 15 mm shallower than adjoining worktops (to provide a gap for tiles and movement)
- Width of the worktop = width of the lift
- Sink bowls with a maximum height of 120 mm can be integrated
- Electronics and motor system "Plug and Play"
- Width of front = width of lift -4 mm  
Height of front: 103 mm, fittings enclosed
- Cover panels can hide installations under the worktop 2 pcs width = width of lift -10 mm, height 438 mm, thickness 12-20 mm

### Standard equipment

- Factory-mounted aluminium system with movable and tiltable brackets
- Floor-mounted motors
- Safety switch

### Article Info

**Art.no**  
6310HA-219

**Description**  
Baselift 6310HA - 219,0 cm

**EAN**  
7340193102789

# Specifications

## Installation

Floor-mounted

## Front height

103 mm

## Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. top board)

## Speed level

30 mm/sec.

## Operation

Recessed mounted button or radio control

## Safety

The safety strip is placed under the front edge of the worktop.  
If anything touches the safety strip, the lifting unit stops

## Electrical connection

Plug for 230 V, max 5.0A

## Plumbing connections

Connection is made with flexible hoses

## Lifting force

100kg

## IP-class

IP 20

## Frame depth

560-590 mm from wall

## Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

## Width worktop

Width = width of the lift

## Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

## Space to wall / adjoining cabinet

5 mm

## Space to wall (for tiles)

15 mm

## Tiling

From 700 mm above floor (alternatively all the way down to the floor)

## Delivery modules

Ready-mounted worktop incl. safety switch, motors

## Fittings supplied

Bracket for fronts

## Material

Aluminium frame

## Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

