

MANULIFT 6380LA - 120,0 cm



MANULIFT 6380L is a manually adjustable worktop unit. Under the worktop, space is left for the knees and legs. Installations under the worktop, (brackets, water, sewers), can be concealed by telescopic cover panels which gives the kitchen a neat look. The height is adjustable by 300 mm at 25 mm intervals.

A built-in gas spring facilitates the adjustment. The lift is prepared in the factory to facilitate easy installation.

Functions and advantages

- Can be equipped with hob
- 30 cm height adjustment
- Adjustable depth, 56 – 59 cm from wall
- Frame in aluminium. Prepared from factory. Movable (sideward) and angle adjustable consoles.
- Brackets and screws for installation of fronts and worktop are included in the delivery

Article Info

Art.no
6380LA-120

Description
MANULIFT 6380LA - 120,0 cm

EAN
7340193104110

Specifications

Installation

Wall-mounted

Front height

40 mm

Height adjustment

Manually adjustable by 300 mm in intervals of 25 mm (700-1000 mm excl. top board)

A built-in gas spring facilitates height adjustment:

Pull out the locking pin, adjust the height with the help of the gas spring.

Lock the position with the locking pin.

Max load

100 kg

Frame depth

560-590 mm from wall

Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

Width worktop

Width = width of the lift

Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Delivery modules

Ready-mounted worktop incl. wall-mounted brackets

Fittings supplied

Bracket for fronts and top board

Material

Aluminium frame

Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

