

SIDELIFT 6400HA, 209,0 cm

- Anthracite, RAL 9004



SIDELIFT 6400 is a straight, motorised worktop lift. Cabinets can be hung under the entire lift or under certain sections. Powerful motors (400 kg lifting power) are located on the short sides. The motors work steplessly and adjust the worktop quickly and quietly to the desired height. The lift is equipped with a reliable safety system that guarantees safe operation without any risk of pinching. The lift is prepared in the factory to facilitate easy installation.

The lift can be integrated with kitchens from any kitchen manufacturer.

Functions and advantages

- Motorised, straight worktop lift with side motors
- Cabinets can be hung under the entire worktop or under certain parts
- Height-adjustable 70-100 cm above the floor (excl. worktop)
- 400 kg lifting power
- Safety switch under cabinets and where there are spaces for knees
- Control button, Mini located in motor units

Useful information

- Fittings for worktop enclosed
- Width of the worktop = width of the lift
- The worktops depth must be 15 mm shallower than adjoining worktops (*to provide a gap for tiles and movement*)
- Sink bowls with a maximum height of 120 mm can be integrated
- Electronics and motor system "Plug and Play"
- Width of front = width of lift - 94 mm Height of front = 103 mm. Fittings enclosed
- Cover panels can hide installations under the worktop Width = width of lift - 410 mm
2 pcs height 438 mm, thickness 12-20 mm

Standard equipment

- Factory-mounted aluminium system
- Floor-mounted motors
- Control button

Article Info

Art.no	Description
6400HA-209-07	SIDELIFT 6400HA, 209,0 cm

EAN
7340193101706

- Anthracite, RAL 9004

Installation

Floor mounted

Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. top board)

Speed level

20 mm/sec.

Operation

Control button, Mini is located in the motor units (left and right side)

Safety

There are safety switches under the cabinet and under the front in spaces for knees. The function of the safety switch is to stop the movement if it comes into contact with any object.

Electrical connection

Plug for 230 V, 2 x 5A

Plumbing connections

Connection is made with flexible hoses

Lifting force

400 kg

IP-class

IP 20

Frame depth

561 mm

Front height

103 mm

Dimensions cover plates

Width = Width of lift -410 mm

2 pcs Height 438 mm

Thickness 12 mm

Width worktop

Width = width of the lift

Depth worktop

15 mm shallower than worktops on fixed cabinets

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Delivery modules

1 package with motor units. 1 package with length-dependent beams

Material

Motor units in lacquered. Aluminium beams

Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

