

Draft specification



Baselift 6310HA - 60,0 cm
Manufacturer: Granberg

Article Info

BASELIFT 6310HA is a straight, motorised worktop lift with floor-mounted motors. Under the worktop, space is left for the knees and legs. Installations under the worktop (motors, water, sewers) can be concealed by telescopic cover panels which gives the kitchen a neat look. The motors work steplessly and adjust the worktop quickly and quietly to the desired height. The lift is equipped with a reliable safety system that guarantees safe operation without any risk of pinching. The lift is prepared in the factory to facilitate easy installation.

The lift can be integrated in kitchens from any kitchen manufacturer.

Art.no	Description	EAN
6310HA-060	Baselift 6310HA - 60,0 cm	7340193102475

Specifications

Installation

Floor-mounted

Front height

103 mm

Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. top board)

Speed level

30 mm/sec.

Operation

Recessed mounted button or radio control

Safety

The safety strip is placed under the front edge of the worktop.
If anything touches the safety strip, the lifting unit stops

Electrical connection

Plug for 230 V, max 5.0A

Plumbing connections

Connection is made with flexible hoses

Lifting force

100kg

IP-class

IP 20

Frame depth

560-590 mm from wall

Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

Width worktop

Width = width of the lift

Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Delivery modules

Ready-mounted worktop incl. safety switch, motors

Fittings supplied

Bracket for fronts

Material

Aluminium frame

Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

