

Draft specification



MANULIFT 6350HA - 219.0 cm
Manufacturer: Granberg

Article Info

MANULIFT 6350H is a manually adjustable worktop unit. Under the worktop, space is left for the knees and legs. Installations under the worktop, (brackets, water, sewers), can be concealed by telescopic cover panels which gives the kitchen a neat look. 30 cm stepless height adjustment by a cranked winding handle. The lift is prepared in the factory to facilitate easy installation.

The lift can be integrated with kitchens from any kitchen manufacturer.

Art.no	Description	EAN
6350HA-219	MANULIFT 6350HA - 219.0 cm	7340193113815

Specifications

Installation

Wall-mounted

Front height

103 mm

Height adjustment

30 cm stepless height adjustment by a cranked winding handle

Number of turns / cm height adjustment

3.3

Plumbing connections

Connection is made with flexible hoses

Max load

100 kg

Frame depth

560-590 mm from wall

Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

Width worktop

Width = width of the lift

Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Delivery modules

Ready-mounted worktop incl. wall-mounted brackets

Fittings supplied

Bracket for fronts and top board

Material

Aluminium frame

Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

