

## Draft specification

**SIDELIFT 6400HA, 309,0 cm**

- White, RAL 9003

**Manufacturer:** Granberg

### Article Info

**SIDELIFT 6400** is a straight, motorised worktop lift. Cabinets can be hung under the entire lift or under certain sections. Powerful motors (400 kg lifting power) are located on the short sides. The motors work steplessly and adjust the worktop quickly and quietly to the desired height. The lift is equipped with a reliable safety system that guarantees safe operation without any risk of pinching. The lift is prepared in the factory to facilitate easy installation.

The lift can be integrated with kitchens from any kitchen manufacturer.

**Art.no**  
6400HA-309-01

**Description**  
SIDELIFT 6400HA, 309,0 cm  
- White, RAL 9003

**EAN**  
7340193101997

## Installation

Floor mounted

## Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. top board)

## Speed level

20 mm/sec.

## Operation

Control button, Mini is located in the motor units (left and right side)

## Safety

There are safety switches under the cabinet and under the front in spaces for knees. The function of the safety switch is to stop the movement if it comes into contact with any object.

## Electrical connection

Plug for 230 V, 2 x 5A

## Plumbing connections

Connection is made with flexible hoses

## Lifting force

400 kg

## IP-class

IP 20

## Frame depth

561 mm

## Front height

103 mm

## Dimensions cover plates

Width = Width of lift -410 mm

2 pcs Height 438 mm

Thickness 12 mm

## Width worktop

Width = width of the lift

## Depth worktop

15 mm shallower than worktops on fixed cabinets

## Space to wall / adjoining cabinet

5 mm

## Space to wall (for tiles)

15 mm

## Tiling

From 700 mm above floor (alternatively all the way down to the floor)

## Delivery modules

1 package with motor units. 1 package with length-dependent beams

## Material

Motor units in lacquered. Aluminium beams

## Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

